

**NOYES®**

### CSS1-MM Contractor Series Dual LED Light Source



The NOYES CSS1-MM from AFL is a palm-sized, cost-effective dual LED light source designed for performing insertion loss measurements on multimode fiber optic links when used with an optical power meter. When paired with an optical fiber identifier, the CSS1-MM may be used for fiber identification. The LED output is stabilized to ensure accurate test results per current TIA/EIA requirements. Weighing only 0.4 lb, this light source is ideal for field use.

The CSS1-MM features 850 nm and 1300 nm LED output from a single output port and is easy to operate. Each wavelength may be transmitted individually at CW or with user selectable modulated Tone. The optical output port is equipped with a fixed SC connector. A large LCD display with backlight shows emitted wavelengths [nm], tone frequency [Hz], and indicates a low battery condition. The CSS1-MM offers a five-minute auto-off feature and long battery life from common AA alkaline batteries.

The CSS1-MM is fully N.I.S.T. traceable.

#### Features

- Palm-sized, rugged, lightweight
- Dual wavelengths from a single port
- CW and modulated Tone
- 270, 330, 1000, 2000 Hz Tone
- Large LCD with backlight
- Automatic power-off function
- Battery gauge
- Long battery life with AA alkaline
- Free 50  $\mu$ m and 62.5  $\mu$ m mandrels
- Cost-effective, easy to use
- N.I.S.T traceable

#### Applications

- Certify 50 or 62.5  $\mu$ m multimode fiber links for any 850 or 1300 nm application, including Gigabit Ethernet (GBE), per TIA/EIA standards
- Fiber identification prior to splicing

**NOYES®**  
**CSS1-MM Contractor Series Dual LED Light Source**

**Specifications <sup>a</sup>**

OPTICAL	CSS1-MM (SINGLE PORT)	
Output Wavelength	850 nm ±20 nm	1300 nm +40/-60 nm
Spectral Width (max)	35 nm	170 nm
Output Power	≥ -20.0 dBm into 62.5/125 fiber	
Emitter Type	LED, Class I FDA 21 CFR 1040.10 and 1040.11, IEC 60825-1: 2007-03	
Output Stability	± 0.1 dB over 1 hour (after 30 seconds typically) ± 0.15 dB over 8 hours (after 30 seconds typically)	
Tone Output	270, 330, 1000, 2000 Hz	
GENERAL		
Output Connector	SC	
Power	2 x AA batteries	
Battery Life	30 hours typical	
Operating Temperature	-10 °C to 50 °C, 90 % RH (non-condensing)	
Storage Temperature	-30 °C to 60 °C, 90 % RH (non-condensing)	
Size (H x W x D)	11.4 x 6.4 x 3.2 cm (4.5 x 2.5 x 1.3 in)	
Weight	0.18 kg (0.4 lb)	

**Note:**

a. All specifications valid at 25 °C unless otherwise specified.

**Ordering Information**

INCLUDES	AFL NO.
2 x AA batteries, user's guide, and carry case.	CSS1-MM

**Authorized Channel Partner**



United States  
 Customer Service  
 1.800.321.5298  
 1.603.528.7780  
 www.AFLglobal.com

Europe, Middle East, Africa  
 Max Penfold  
 Max.Penfold@AFLglobal.com  
 +44 1799 542 840  
 +44 7802 839 160

Middle East  
 Ahmed El Sakaty  
 Ahmed.ELsakaty@AFLglobal.com  
 +20 106 451 523

Africa (Sub Sahara)  
 Nicholas Cole  
 Nicholas.Cole@AFLglobal.com  
 +44 7702 005 590

Greater China  
 Dai Liu  
 Dai.Liu@AFLglobal.com  
 +86 133 1101 4533

Asia-Pacific (non-China)  
 Saw Biing Huei  
 Biing.Saw@AFLglobal.com  
 +65 9791 3398