

Application Systems

Optics & Optical Coatings

Opto-Mechanics

Bases

Manual Stages

Actuators & Adjusters

Motorized Stages

Light Sources & Laser Safety

Index

Guide

Vibration Isolation Systems

Optical Tables

Darkrooms/ Dark Boxes

Optical Bases

Posts


Brackets

Adapters

Tools

Black Anodized Aluminum Base Plates.

Can be used on small vibration isolators or laboratory benches for optical systems.




- Attached grips allow easy moving and storage.
- M4 or M6 tapped through holes are arranged on 25mm×25mm spacing. 1/4-20UNC tapped through holes are on 25.4 mm x 25.4 mm spacing
- Flatness is 0.2mm.

Guide

- Each baseplate comes with two aluminum handles.
- Custom sizes are available contact our Sales Division for more information.

**Outline Drawing****OBC-3045 Series**


- Hexagon socket head cap screw (stainless steel construction) M6×10...4 screws (3045, 3045-M6)
Hexagon socket head cap screw (stainless steel construction) 1/4-20UNC×3/8...4 screws (3045-1/4UU)



Part Number	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F
OBC-3045	425	275	25	250	400	M4
OBC-3045-M6	425	275	25	250	400	M6
OBC-3045-1/4UU	431.8	279.4	25.4	254	406.4	1/4-20UNC

OBC-4560 Series


- Hexagon socket head cap screw (stainless steel construction) M6×10...4 screws (4560-M6)
Hexagon socket head cap screw (stainless steel construction) 1/4-20UNC×3/8...4 screws (4560-1/4UU)



Part Number	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F
OBC-4560	575	425	25	400	550	M4
OBC-4560-M6	575	425	25	400	550	M6
OBC-4560-1/4UU	584.2	431.8	25.4	406.4	558.8	1/4-20UNC

OBC-4545 Series

- Hexagon socket head cap screw (stainless steel construction) M6×10...4 screws (4545, 4545-M6)
Hexagon socket head cap screw (stainless steel construction) 1/4-20UNC×3/8...4 screws (4545-1/4UU)



Part Number	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F
OBC-4545	425	425	25	400	400	M4
OBC-4545-M6	425	425	25	400	400	M6
OBC-4545-1/4UU	431.8	431.8	25.4	406.4	406.4	1/4-20UNC

SpecificationsPrimary material: Aluminum
Finish: Black Anodized

Part Number			Size [mm]	Weight [kg]
Tapped Holes on Top Surface				
M4	M6	1/4-20UNC		
OBC-3045	OBC-3045-M6	OBC-3045-1/4UU	300×450	3.6
OBC-4545	OBC-4545-M6	OBC-4545-1/4UU	450×450	5.4